



**EBSProducts.com**

Ph:714-896-6700

sales@ebsproducts.com

9-25

## 1000-0070- Coolant Service Specifications

- A reverse flow Coolant flush and change service machine (or normal flow using D-Gas Adapters included), covers 99% of vehicles.
- 110 vac powered, fuse protected, converted to 12 vdc operation- 22 ft. power cord with power cord holder attached to cabinet.
- Std Adapters and By-Pass adapter connect to disconnected upper Radiator Hose for service.  
**Engine OFF.**
- Std Hose sizes: 1.0, 1.25, 1 3/8, 1.5, 1.75, 2.0, 2.25 and 2.5”.
- D-Gas/Overflow Adapters allow the service to be performed thru the Overflow Tank-no need to remove any Shroud. - **Engine ON.**
- D-Gas Hose sizes .25, 5/16, 3/8 and .50”.
- Easy to use, 3 - Lighted Electrical Switches control the service.
- Separate Fill and Vacuum pumps each rated at one gallon per minute.
- 8- Gal. New Fluid Tank and 8-Gal. Waste Tank protected in cabinet.
- Separate Fill and Vacuum pumps each rated at one gallon per minute.
- A Prime Valve between service hoses to prime pumps or empty remaining new fluid to the waste tank if desired.
- Easy top fill of new coolant tank.
- Level Sensor stops fluid flow when ½ G of new fluid remains.
- A third 12 vdc, 3.7 GPM rated pump, switched on the rear of the equipment for emptying the waste tank.
- A controllable handgun for vacuuming.

**2-Year Warranty.**

### Machine Dimensions

Height - 44in.	Depth - 23in.	Width - 24in.
----------------	---------------	---------------

Weight - 88lbs.	Shipping Weight - 132lbs.
-----------------	---------------------------

