



EB-20 #1000-0020 Brake Fluid Service Specifications

- Self-contained brake fluid flush, change and bleed equipment-Patented.
- Computer controlled through a touch pad system and LCD screen.
- 110 vac powered, switch and fuse protected, converted to 12 vdc for operation for all internal parts.
- 22 ft. heavy duty power cord with power cord holder attached to cabinet.
- Equipment cabinet made from heavy-duty industrial grade polyethylene.
- Cabinet contains a built-in sturdy handle with locking front wheels and large 8" rear wheels for safe and easy movement.
- Cabinet insert for 32oz to 64oz brake fluid bottle.
- Adapters are easily connected and cover 98% of vehicles – additional-Specialty/convenience adapters are available.
- Adapters vent air out of the master cylinder reservoir to prevent air from entering the brake system.
- Includes controllable handgun wand for vacuuming fluid from the master cylinder – can also be used for fill needs.
- All service hoses have a 1 to 3ft. clear section for visual ability, with a 10ft. fill hose, an 8ft. vac hose, 2-10ft. front bleeder hoses and 2-17ft. rear bleeder hoses.
- A combination of pressure (15-20 psi) at the M/C reservoir and vacuum at all 4 bleeder valves provides a safe and effective fluid flush, extraction, fill and bleed of the brake system – bleed sequencing not necessary.
- Separate 12-volt pressure and vacuum pumps each rated at one gallon per minute pumping capacity to provide a flow of approximately ½ quart per minute.
- Operation, pump pressures, no flow warnings (service STOPS if no more fluid is available), waste tank levels, service time, service count, controlled and monitored by the computer.
- A sensor in the waste tank advises when the 7-gallon waste tank requires emptying. A separate waste pump, switch and waste hose is accessed at the rear of the equipment.



Machine Dimensions	Machine Weight: 88lbs
Height: 44in	Shipping Weight: 132lbs
Depth: 23in	
Width: 24in	